

TENAX LABOR



EXTRUDED NET

PHYSICAL AND DIMENSIONAL CHARACTERISTICS

Polymer		HDPE	
Mesh shape		OVOIDAL	
Packaging		ROLLS WRAPPED IN PE FILM	
Color		ORANGE	
MD pitch	mm	70,0	
TD pitch	mm	50,0	
Unit weight	g/m ²	85	
Roll width	m	1,00	1,20
Roll length	m	50	50,0
Covered area	m ²	50	60,0
Roll diameter	m	0,14	0,14
Roll volume	m ³	0,02	0,03
Roll weight	kg	4,5	5,3

MECHANICAL CHARACTERISTICS

Tensile strength MD	kN/m	0,50	
Tensile strength TD	kN/m	0,40	
Yield point elongation MD	%	4,0	
Yield point elongation TD	%	3,0	

The data contained in this publication are based on the knowledge available at the time of printing and may be subjected to amendments due to changes of the methods of testing and/or manufacturing. All dimensions and properties are reported as typical values.

TENAX nets are thermoplastic products subjected to shrinkage and deformations. MD: longitudinal direction. TD: transversal direction.

Tenax SpA Quality System has been assessed and registered in agreement with ISO 9001:2000 Standard.

TENAX[®]

www.tenax.net