

# TENAX SIGNAL 150



---

## MONO - ORIENTED NET

---

---

### PHYSICAL AND DIMENSIONAL CHARACTERISTICS

---

Polymer		PP
Mesh shape		OVOIDAL
Packaging		ROLLS WRAPPED WITH POLYETHYLENE FILM
Color		YELLOW    NAVY BLUE    RED
MD pitch	mm	60,0
TD pitch	mm	12,0
Unit weight	g/m <sup>2</sup>	80
Roll width	m	0,50
Roll length	m	250,0
Covered area	m <sup>2</sup>	125,0
Roll diameter	m	0,27
Roll volume	m <sup>3</sup>	0,038
Roll weight	kg	10,4
Inner tubular diameter	mm	45

---

### MECHANICAL CHARACTERISTICS

---

Tensile strength MD	kN/m	4,0
Tensile strength TD	kN/m	
Yield point elongation MD	%	8,0
Yield point elongation TD	%	

---

The data contained in this publication are based on the knowledge available at the time of printing and may be subjected to amendments due to changes of the methods of testing and/or manufacturing. All dimensions and properties are reported as typical values.

TENAX nets are thermoplastic products subjected to shrinkage and deformations. MD: longitudinal direction. TD: transversal direction.

Tenax SpA Quality System has been assessed and registered in agreement with ISO 9001:2000 Standard.

---

**Note:** Available also with a textural plastic band and/or an anticorrosive metallic band.

---

**TENAX**<sup>®</sup>