

TENAX FVP

Tipo: **Biodegradable pre-sown**
Biotextile



TENAX **FVP** is a biodegradable pre-sown biotextile designed for protection and growing of grass on slopes subject to surface erosion.

Typical application

Erosion control and progressive growing, slopes, canals.

PHYSICAL CHARACTERISTICS	TEST METHOD	UNIT	TENAX FVP	NOTES
STRUCTURE			BIOTEXTILE	
COLOR			GREEN	
COMPONENTS			VISCOSE –SEEDS – FERTILIZERS	
CHARACTERISTICS			100% BIODEGRADABLE	
SEEDS			GRAMINACEOUS + LEGUMINOUS	
PACKAGING	ISO 10320		ROLLS WITH IDENTIFICATION LABEL	

DIMENSIONAL CHARACTERISTICS	TEST METHOD	UNIT	TENAX FVP	NOTES	
MASS per UNIT AREA	ISO 9864	g/m ²	250	250	a,c,d
THICKNESS at 2 kPa	ISO 9863	mm	2.0	2.0	a
ROLL WIDTH		m	1.05	2.15	a,d
ROLL LENGTH		m	100	50	a,d
ROLL DIAMETER		m	0.53	0.35	a
ROLL VOLUME		m ³	0.36	0.28	a
ROLL GROSS WEIGHT		kg	26.7	27.1	a,d

NOTES:

- a) Typical Value
- b) MD : Machine Direction
TD : Cross-Machine Direction
- c) seeds and fertilizers are included
- d) Tolerance: ±10%

All specifications listed are subject to change without notice



The TENAX Laboratory has been operational since 1980 and has been continuously improved with the purpose of assuring unequalled technical development of the products and accurate Quality Control.

The TENAX Laboratory can perform mechanical, hydraulic and durability tests, according to the most important international standards like ISO, CEN, ASTM, DIN, BSI, UNI.

TENAX SpA Geosynthetics Division

Via dell'Industria, 17
I-23897 Viganò (LC) ITALY
Tel. +39 039.9219307
Fax +39 039.9219200
e-mail: geo@tenax.net
Web Site: www.tenax.net

