

# TENAX COAT FILM PLUS

## Protective film

PHYSICAL CHARACTERISTICS	TEST METHOD	UNIT	COAT FILM PLUS			NOTES
COMPOSITION			POLYETHYLENE			-
COLOUR			CLEAR			-
PACKAGING			PE BAG			-

DIMENSIONAL CHARACTERISTICS	TEST METHOD	UNIT	COAT FILM PLUS			NOTES
THICKNESS		mm	0.15			-
UNIT WEIGHT		g/m <sup>2</sup>	140.0			-
FILM WIDTH		m	2.0	2.0	1.6	
ROLL WIDTH		m	1.0	4.0	6.0	-
ROLL LENGTH		m	100.0	100.0	70.0	-
COVERED AREA		m <sup>2</sup>	200.0	400.0	420.0	-
ROLL DIAMETER		m	0.22	0.22	0.28	-
ROLL VOLUME		m <sup>3</sup>	0.05	0.1	0.12	-
ROLL WEIGHT		Kg	30.0	60.0	61.8	-
DIAMETRO INTERNO ANIMA		m <sup>3</sup>	76.5			

### NOTES:





Just Indicating

*The data contained in this publication are based on the knowledge available at the time of printing and may be subjected to amendments due to changes of the methods of testing and/or manufacturing. All dimensions and properties are reported as typical values. Tenax nets are thermoplastic products subjected to shrinkage. MD: longitudinal direction. TD: transversal direction. Tenax Spa Quality System has been assessed and registered in agreement with ISO 9001:2008 Standard*

TENAX Spa Quality System has been assessed and registered in agreement with ISO:9001:2008 by SGS Italy and SGS UK.



The TENAX Laboratory has been operational since 1980 and has been continuously improved with the purpose of assuring unequalled technical development of the products and accurate Quality Control. The TENAX Laboratory can perform mechanical, hydraulic and durability tests, according to the most important international standards like ISO, CEN, ASTM, DIN, BSI, UNI.



**TENAX SpA**  
Via dell'Industria, 3  
23897 Viganò (LC)  
Tel. +39 039.9219300  
Fax +39 039.9219290  
customer.service@tenax.net